



SOCIETY FOR MATERIALS AND STRUCTURES TESTING OF SERBIA
CONTEMPORARY CLAY PRODUCTS INDUSTRY ASSOCIATION OF SERBIA

XXVIII CONGRESS DIMK and IX CONGRESS SIGP

with INTERNATIONAL SYMPOSIUM

ON RESEARCHING AND APPLICATION OF CONTEMPORARY ACHIEVEMENTS
IN CIVIL ENGINEERING IN THE FIELD OF MATERIALS AND STRUCTURES



Divčibare, October 19-21, 2022.

M. R. Vasić¹
Z. Radojević²

**DODATNA VALIDACIJA TEORIJE TRANSPORTA VLAGE TOKOM
IZOTERMSKOG SUŠENJA**

Rezime: Program „GetData-Graph digitalizer“ je korišćen za očitavanje koordinata tačaka sa dijagrama krivih sušenja i skupljanja preuzetih iz literature. Prikupljeni podaci su dalje obrađivani uskladu sa teorijom transporta vlage tokom izotermiskog sušenja. Utvrđeno je da je oblik prognoznih krivi određen sa literaturno prikupljenim podacima sličan i uporediv sa teorijskom krivom Deff - MR. Karakteristične tačke koje definišu redosled i raspored medusobne interakcije mehanizama sušenja prikazane na teorijskoj prognoznoj krivi uočene su i na krivama preuzetim iz različitih naučnih radova, bezobzira na činjenicu što se metod proračuna zavisnosti Deff - MR prikazan u literaturi razlikovao od postupka na kome je zasnovana teorija transporta vlage tokom izotermiskog sušenja. Upravo ova činjenica je potvrdila univerzalni karakter novorazvijene teorije sušenja.

Ključne reči: sušenje, efektivni koeficijent difuzije, keramički crepovi, skupljanje

VERIFICATION OF THE DEVELOPED DRYING THEORY

Abstract: The program "GetData-Graph digitizer" was used as a tool for reading the coordinates from the drying and shrinkage curve diagrams taken from the literature. The collected data were further processed in accordance with the theory of moisture transport during isothermal drying. It was found that the resulting prognostic Deff - MR curves shape was similar and comparable to the theoretical one. It is important that all the transition points of the internal mechanisms registered on theoretical curve are present and can be seen in the same way on all the literatureally taken figures, regardless of the fact that the calculation method for the determination of time dependent effective diffusion coefficient were different.

Key words: drying, effective diffusivity, clay tile, shrinkage

¹ dr Miloš Vasić, dip.inž. tehnologije, naučni saradnik, Bulevar vojvode Mišića 43, milos.vasic@institutims.rs

² dr Zagorka Radojević, dip.inž tehnologije, naučni savetnik, Bulevar vojvode Mišića 43, zagorka.radojević@institutims.rs

- [22] I.I.R.Lopez, H.R.Espinoza, A.P.Lozada, A.M.G.Alvarado: „Analytical model for moisture diffusivity estimation and drying simulation of shrinkable food products“, Journal of Food Engineering 108 (2012) 427-435.
- [23] G.Efremov, T.Kudra: „Model-Based Estimate for Time-Dependent Apparent Diffusivity“, Drying technology 23 (2005) 2513-2522
- [24] M.L.Batista, R.A.Cezar, L.A.A.Pinto: „Diffusive model with variable effective diffusivity considering shrinkage in thin layer drying of chitosan“, Journal of Food Engineering 81 (1) (2007) 127-132.
- [25] S.Azzouz, A.Guizani, W.Joma, A.Belghith: „Moisture diffusivity and drying kinetic equation of convective drying of grapes“, Journal of Food Engineering 55 (2002) 323-330.
- [26] A.Sander: „Thin layer drying of porous materials: Selection of the appropriate mathematical model and relationships between thin-layer models parametres“, Chemical Engineering and Processing, 46 (2007) 1324-1331.
- [27] A.Sander, J.P.Kardum, A.Glasnović: „Drying of Solid, Estimation of the mathematical model parameters“, The Canadian Journal Of Chemical Engineering 88 (2010) 822-829.